CL 97-1376



Home
Instrument
Applications
Data Products
Validation
Obtaining Data
Team
Documents
Phone Book
Links
News

Spectral Library

Airborne Simulator

ASTER





ASTER (Advanced Spaceborne Thermal Emission and Reflection Radiometer) is an imaging instrument that is flying on <u>Terra</u>, a satellite launched in December 1999 as part of NASA's <u>Earth Observing System (EOS)</u>. ASTER will be used to obtain detailed maps of land surface temperature, emissivity, reflectance and elevation. The EOS platforms are part of NASA's <u>Earth Science Enterprise</u>, whose goal is to obtain a better understanding of the interactions between the biosphere, hydrosphere, lithosphere and atmosphere.

ASTER is the only high spatial resolution instrument on the Terra platform. It will be used with MODIS, MOPITT, MISR and CERES which monitor the Earth at moderate to coarse spatial resolutions. ASTER's ability to serve as a 'zoom' lens for the other instruments will be particularly important for change

detection, calibration/validation and land surface studies.


The ASTER instrument was built in Japan for the Ministry of International Trade and Industry. A Joint US/Japan Science Team is responsible for instrument design, calibration, and validation.

The primary objective for the ASTER mission is to:

 Obtain <u>high spatial resolution</u> global, regional and local images of the Earth in 14 colors (spectral bands.)



Download The ASTER Brochure (pdf 5310k)



[Home] [Applications] [Data Products] [Validation] [Obtaining Data] [Team] [Documents] [Spectral Library] [Airborne Simulator] [Phone Book] [Links] [News]








ALL RIGHTS RESERVED
Copyright 1998 1999 2000 California Institute of Technology
U.S. Government Sponsorship Acknowledged under NAS7-1260

Questions? Comments? Contact: <u>Howard L Tan</u> or <u>Simon J Hook</u>
This Page has been hit #25332 times since 09/17/99.
Last Changed: May 11, 2000

Table of Contents


ASTER

Advanced Spaceborne Thermal Emission and Reflection Radiometer














Terra Instruments

ASTER - Advanced Spaceborne Thermal Emission and Reflection Radiometer

CERES - Clouds and Earth's Radiant Energy System

MISR - Multi-angle Imaging Spectro Radiometer

MODIS - Moderate Resolution Imaging Spectro-Radiometer

MOPITT - Measurements of Pollution in the Troposphere





Terra Orbit Parameters

Orbit Sun Synchronous

Descending Node

Time of Day 10:30 am


Altitude 705 km

Inclination 98.2°

Repeat Cycle 16 days











ASTER Instrument Overview

- ASTER is an international effort:
 - Japanese government is providing the instrument under MITI (Ministry of International Trade and Industry) and is responsible for Level 1 data processing
 - Will fly on NASA's Terra platform
 - Science team consists of Japanese,
 American, Australian, and French scientists






ASTER Instrument

- <u>Advanced Spaceborne Thermal Emission</u> and <u>Reflection Radiometer</u>
- 1999 launch on Terra
- Joint Japan/US effort
- 15m visible, 30 m swir, 90 m tir
- 60 km swath
- < 16 day repeat cycle





















ASTER Bands







ASTER Science Team

Consists primarily of Japanese and US members

Conducts scientific research related to EOS goals using ASTER data

Provides scientific guidance to hardware builders:

- functional requirements
- design issues
- calibration
- modes of operations





ASTER Science Team

Selects algorithms for higher level standard products

Produces software for standard products

Conducts joint calibration and validation exercises

Conducts mission operations, scheduling, and mission analysis





ASTER Instrument Operations

- ASTER has a limited duty cycle which implies decisions regarding usage must be made
- Observation choices include targets, telescopes, pointing angles, gains, day or night observations
- Telescopes capable of independent observations and maximum observation time in any given orbit is 16 minutes
- Maximum acquisitions per day

Acquired ~750

Processed ~330





ASTER Instrument Operations

- Number of pointing changes over life of mission limited to 10,000 -- approximately 1 per 2.5 orbits for VNIR and SWIR
- Pointing changes to be made during nighttime part of orbit
- These limitations allow a maximum of 1.7 million scenes over the life of the mission





Science Prioritization of ASTER data acquisition

- NASA HQ, GSFC, and MITI have charged the Science Team with developing the strategy for prioritization ASTER data acquisition
- Must be consistent with EOS goals, the Long Term Science Plan, and the NASA-MITI MOU
- Must be approved by EOS Project Scientist





Global Data Set

- A one-time acquisition
 - All land surfaces, including stereo
 - Maximize high sun
 - "Optimal" gain
- Consists of pointers to processed and archived granules which:
 - Meet the minimum requirements for data quality
 - Are the "best" acquired satisfying global data set criteria
- Science Team has prioritized areas for acquisition (high, medium and low)



Regional Data Sets

- Focus on specific physiographic regions of Earth, usually requiring multi-temporal coverage
- Acquisitions are intended to satisfy multiple users, as opposed to specific requirements of individual investigator or small team
- Defined by the ASTER Science Team in consultation with other users (e.g., EOS interdisciplinary scientists)
- Science team provides prioritization (relative to other regional data sets) on a case-by-case basis






Targeted Observations

- Targeted observations are made in response to Data Acquisition Requests (DARs) from individual investigators or small groups for specific research purposes
- Japanese Instrument Control Center (ICC) does prioritization of DAR based on guidelines provided by Science Team
- Targeted observation may also be used to satisfy the global data set or regional data set acquisition goals, where appropriate







How Will I Get ASTER Data

• Browse the archive: use the EOS Data Gateway (EDG) to find what data have already been acquired. Order data products desired:

http://harp.gsfc.nasa.gov/~imswww/pub/imswelcome/

• Submit a Data Acquisition Request: First become an authorized user; then request satellite obtain your particular data





Scientists Authorized to Submit DARs

- ASTER Science Team
- Other EOS Instrument Team members
- EOS Interdisciplinary Science Teams
- Other scientists "registered" by Japan





Authorizing Non-EOS Users to Request ASTER Acquisition

U.S. PROCESS FOR AUTHORIZING NON-EOS ASTER USERS:

- Interested ASTER user sends proposal electronically
 - Proposal forms, and ASTER information, will be available on-line
 - Proposal (1-2 pages long) can be submitted electronically <u>at any time</u>
 - Each proposal includes estimate of number of ASTER scenes
 - Proposals evaluated by committee: ASTER Team Members, NASA HQ, external scientists
 - Most proposals evaluated within few weeks
 - Notice of acceptance or rejection sent by e-mail
- Once authorized, new user can request that ASTER acquire new data
 - U.S. users submit ASTER DARs via DAR Clients, provided by ECS

SPECIFIC NUMBER OF ASTER SCENES ALLOCATED TO EACH SUCCESSFUL PROPOSAL

Scenes are allocated based on estimated requirements (included in proposal)





ASTER Standard Data Products

Level-1 Data

Decorrelation Stretch: VNIR, SWIR, TIR

Brightness Temperature

Surface Reflectance/Radiance: VNIR & SWIR

Surface Reflectance/Radiance: TIR

Surface Emissivity


Surface Kinetic Temperature

Digital Elevation Model






14 radiance channels




















Temperature image from temp-emissivity separation











Emissivity images from T-E separation







Emissivity images from T-E separation









(top) VNIR-SWIR + ASTER DEM (bottom) TIR + ASTER DEM

60 x 60 km image






Popocatepetl Volcano, Mexico








SO2 Recovery







Po River Delta










Po River Delta, Italy NDVI color sliced







Po River Delta







Po River Delta


Po River Delta, Italy ASTER ave T: color sliced







Cloud and Ice Separation Antarctica








Urban Land Use

Scottsdale, AZ







ASTER Web Site: http://asterweb.jpl.nasa.gov



Home instrument

Applications

Validation

Getting Data Team

Documents

Spectral Library

Airborne Simulator

Directory/Search

Contents

What's New

ASTER



ASTER (Advanced Spaceborne Thermal Emission and Reflection Radiometer) is an imaging instrument that will fly on EOS AM-1, a satellite planned for launch in 1999 as part of NASA's Earth Observing System (EOS). ASTER will be used to obtain detailed maps of surface temperature, emissivity, reflectance and elevation. The EOS platforms are part of NASA's Mission to Planet Earth program, whose goal is to obtain a better understanding of the interactions between the biosphere, hydrosphere and atmosphere.

ASTER is the only high spatial resolution instrument on the EOS-AM1 platform. It will be used with MODIS, MOPITT, MISR and CERES which monitor the Earth at moderate to coarse spatial resolutions. ASTER's ability to serve as a 'zoom' lens for the other instruments will be particularly important for change detection, and calibration/validation studies.

The primary objective for the ASTER mission is to:

Obtain high spatial resolution global, regional and local targeted data in 14 channels from the visible through the thermal infrared wavelength regions.

[Frome | f instrument | f populations | [Validation | [Certing Data | [Team | [Documents] [Spectral Library] [Airborne Simulator | [Directory/Search] [Contents] [What's New]







ALL RIGHTS RESERVED

Copyright 1998, California Institute of Technology U.S. Government Sponsorship Acknowledged under NAS7-1260

Questions? Comments? Contact: Howard L Tan or Simon J Hook This Page has been hit #219 times since 12/24/98. Last Changed: May 04, 1999



